



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 051 052 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
08.11.2000 Bulletin 2000/45

(51) Int Cl.7: **H04Q 7/32**

(21) Application number: **99109099.4**

(22) Date of filing: **07.05.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Humaid Darwish Bin Karam
Abu Dhabi (AE)**

(74) Representative:
**Puschmann, Heinz H., Dipl.-Ing.(FH) et al
Puschmann & Borchert,
Patentanwälte,
European Patent Attorneys,
Sendlinger Strasse 35
80331 München (DE)**

(71) Applicant: **Humaid Darwish Bin Karam
Abu Dhabi (AE)**

(54) **Radiotelephone with multiple SIM card readers**

(57) Telecommunication device, particularly a mobile phone, comprising several reading devices (13.1-13.4), connected to a control unit (7), for receiving several data carriers (14.1-14.4) containing different

calling numbers to enable the user of the telecommunication device to be called under several calling numbers using a single telecommunication device, and to place outgoing calls over the least-cost route.




Fig. 1

BEST AVAILABLE COPY

EP 1 051 052 A1

Description

[0001] The invention relates to a telecommunication device and more particularly to a wireless telephone.

[0002] Wireless telephones according to the well known GSM-standard generally comprise a card reader in which a so-called SIM-card has to be inserted before the operation of the telephone is enabled. The SIM-card is issued by the provider and contains the subscriber information of the user and the telephone number under which the user of the telephone can be reached. Therefore, each wireless telephone can be reached only under a single telephone number. On the other hand, because of the decreasing hardware costs of GSM-telephones many people already have several wireless telephones with different telephone numbers for different purposes.

[0003] For example, a manager has one wireless telephone for business calls and another wireless telephone for private calls. This is advantageous since the billing of business calls is often handled by the employer whereas private calls have to be paid by the manager himself.

[0004] Further, for a traveller it might be possible to have one wireless phone with a SIM-card purchased in his home country and a further telephone with a prepaid SIM-card of a provider in the respective country. Therefore, the traveller can still be reached from his home country under his normal telephone number although he can call other people in the respective country using the prepaid SIM-card without payment of long-distance charges.

[0005] However, in order to be reachable under all different telephone numbers one has to carry all wireless phones which is quite inconvenient. Further, a caller has to remember all different telephone numbers to ensure that he can reach the owner of the conventional wireless telephones.

[0006] The problem underlying the present invention is therefore to create a telecommunication device and more particularly a wireless phone, which enables the user to be reached under several different telephone numbers without carrying several telephones.

[0007] This problem is solved by a telecommunication device according to claim 1.

[0008] The general idea of the invention is to provide a telecommunication device with several reading devices for receiving data carriers on which subscriber information is stored wherein each data carrier corresponds to a different telephone number. The term "several" in the sense of the invention means that the telecommunication device according to the invention can have two, three or more reading devices.

[0009] In the preferred embodiment of the invention the data carriers are so-called SIM-cards, whereas the reading devices are SIM-card readers which are already used in conventional wireless phones.

[0010] In a further embodiment of the invention the

control unit of the wireless phone comprises a controllable switch for selecting one of the reading devices respectively one of the data carriers inserted into the reading devices for establishing outgoing calls. Preferably, the controllable switch can be actuated manually, e.g. by pressing predetermined keys on a keyboard. This means the user of the telecommunication device according to this embodiment of the invention can choose the network provider he wants to use for outgoing calls. The manual selection of the provider can be made individually for each outgoing call or alternatively it is possible to select one provider for all outgoing calls.

[0011] In another embodiment of the invention the selection of the reading device respectively the selection of the subscriber information stored on the data carrier inserted into the reading devices is effected automatically by a least-cost-router. In this embodiment the least-cost-router receives the telephone number of the outgoing call and determines the provider who offers the least expensive connection to that number. Then, the least-cost-router actuates the controllable switch to select the corresponding reading device respectively the subscriber information stored on the data carrier which is inserted into that reading device.

[0012] It should be noted that the invention is not limited to wireless telephones but can nevertheless be realized with other kinds of telecommunication equipment, e.g. mobile telephones installed in cars, cordless phones with a stationary main station or mobile fax devices.

[0013] It should further be noted that the data carrier to be inserted into the reading device can also be a permanent memory chip like a ROM or EPROM on which the subscriber information of the user is stored.

[0014] While the specification concludes with claims particularly pointing out and distinctly claiming the subject matter of the invention, it is believed the invention will be understood from the following description taken in connection with the accompanying drawing.

[0015] Figure 1 shows a schematic circuit diagram of the preferred embodiment of the invention.

[0016] The wireless telephone shown in Figure 1 is in accordance with the well known GSM-standard which is commonly used for mobile communication.

[0017] For receiving voice or data from the next cellular base station and for transmitting voice or data to the next cellular base station the telephone comprises an antenna 1 which is connected to a transceiver 2 (RF - radio-frequency unit).

[0018] The telephone further comprises a chipset 3 called CODEC (compression/decompression) connected to the transmitter 2 for compressing the data to be transmitted via the antenna 1 to the next cellular base station and for decompression of the data received from the cellular base station.

[0019] Further, the telephone comprises a conventional loudspeaker 4 for outputting the voice data received via the antenna 1 and also a conventional micro-

phone 5 to input voice data by the user of the telephone. Both the loudspeaker 4 and the microphone 5 are connected to a second chipset 6 (CODEC - compression/decompression) for compression of the voice data to be input via the microphone 5 respectively to decompress the voice data to be output over the loudspeaker 4.

[0020] However, the heart of the telephone is a control unit 7 which is powered by a conventional rechargeable battery 8 and connected to a keyboard 9 (KBD) for inputting data like telephone numbers. The control unit 7 is further connected to a liquid crystal display 10 (LCD) to display user information like menu options or SMS-Messages. Moreover, the telephone comprises a conventional on-board memory 11 for storing outgoing telephone numbers, the users own telephone number, as well as incoming and outgoing SMS messages. The on-board memory 11 further allows copying between the limited memory on SIM-cards and the on-board memory 11.

[0021] The control unit 7 comprises a digital signal processor 12 (DSP) which is a critical component since it coordinates the voice and SMS features of the telephone. It processes speech, handless voice activity detection, as well as dis-continuous GSM transmission and reception.

[0022] However, the components described above are all conventional, whereas the telephone according to the present invention additionally comprises four SIM-card-readers 13.1-13.4 each receiving a single SIM-card 14.1-14.4 on which subscriber information of the user is stored. In this connection it should be noted that the invention is not restricted to a wireless phone with four SIM-card readers as shown in the Figure but can nevertheless be realized with a different number of SIM-card readers, e.g. with two or three SIM-card readers. Therefore, each SIM-card 14.1-14.4 corresponds to a different telephone number under which the user of the telephone can be reached. Therefore, with a wireless telephone according to the present invention it is not necessary any longer to carry several different wireless phones for different purposes since this telephone can be used for all these purposes with different telephone numbers. A further advantage of the telephone according to the invention is that each SIM-card 14.1-14.4 can belong to a different provider of a cellular network thereby giving the user of the telephone the opportunity to choose the cheapest provider individually for each outgoing call.

[0023] In the embodiment shown in Figure 1 the telephone further comprises a controllable switch 15 for selecting one of the SIM-card-readers 13.1-13.4 respectively one of the SIM-cards 14.1-14.4 inserted into the SIM-card-reader in order to choose one provider for outgoing calls. The controllable 15 switch is actuated by a conventional least-cost-router 16 which receives the telephone number to be called and determines the provider who offers the cheapest connection to that telephone number. After this determination the least-cost-router 16

affects the controllable switch 15 accordingly to select the corresponding SIM-card 14.1-14.4.

[0024] It will be apparent to those skilled in the art that many other modifications may be made without departure from the spirit and scope of the invention.

Claims

1. Telecommunication device, particularly a mobile phone, comprising:

an antenna (1) and a transceiver (2) connected therewith for receiving and transmitting digital data,

an output device (4, 10) for outputting data received by the transceiver (2),

an input device (5, 9) for inputting data to be transmitted via the transceiver (2),

a control unit (7) to control the operation of the telecommunication device and

a reading device (13.1) connected to the control unit (7) for receiving a data carrier (14.1) containing subscriber information identifying a calling number under which the user of the telecommunication device can be called,

characterized by that

several reading devices (13.1-13.4) are connected to the control unit (7) for receiving several data carriers (14.1-14.4) containing different calling numbers to enable the user of the telecommunication device to be called under several calling numbers using a single telecommunication device.

2. Telecommunication device according to claim 1, wherein the data carrier is a SIM-card (14.1-14.4) and the reading device is a SIM-card reader (13.1-13.4).
3. Telecommunication device according to claim 1 or 2, wherein the transceiver (2) is a GSM-transceiver.
4. Telecommunication device according to one of the preceding claims, characterized by means (15) for selecting one of the reading devices (13.1-13.4) respectively the subscriber information stored on one of the data carriers (14.1-14.4) for establishing outgoing calls.
5. Telecommunication device according to claim 4, wherein the means (15) for selecting a reading device (13.1-13.4) are manually controllable.

6. Telecommunication device according to claim 4, wherein the means (15) for selecting a reading device (13.1-13.4) for establishing outgoing calls is connected with a least-cost-router (16).

5

7. Telecommunication device according to one of claims 4 to 6, further comprising a display (10) indicating the active reading device (13.1-13.4) respectively the subscriber information stored on the active data carrier (14.1-14.4).

10

15

20

25

30

35

40

45

50

55




Fig. 1



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 10 9099

DOCUMENTS CONSIDERED TO BE RELEVANT

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	EP 0 586 081 A (NOKIA MOBILE PHONES LTD) 9 March 1994	1-5,7	H04Q7/32
Y	* column 2, line 10 - column 3, line 3 * * column 3, line 33 - column 4, line 12 * * column 6, line 4 - line 50 * * abstract; claims 1-5,7-11 *	6	
Y	WO 96 28947 A (NOKIA MOBILE PHONES LTD ;VAZVAN BEHRUZ (FI); JORMALAINEN JANNE (US) 19 September 1996	6	
A	* page 2, line 25 - page 3, line 11 * * abstract; figures 2,5 *	1-3	
A	US 5 802 502 A (MANNING MICHAEL ROBERT WISTOW ET AL) 1 September 1998 * column 1, line 44 - column 2, line 43 * * abstract *	6	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04Q
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 10 June 1999	Examiner Coppieters, S
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 01.92 (P4C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 10 9099

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

10-06-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0586081 A	09-03-1994	GB 2269512 A	09-02-1994
		AU 4435393 A	10-02-1994
		CN 1086367 A	04-05-1994
		DE 69317830 D	14-05-1998
		DE 69317830 T	12-11-1998
		DE 586081 T	15-05-1997
		JP 7312630 A	28-11-1995
WO 9628947 A	19-09-1996	FI 951181 A	14-09-1996
		AU 4881196 A	02-10-1996
		EP 0815701 A	07-01-1998
		JP 11501783 T	09-02-1999
US 5802502 A	01-09-1998	AU 700554 B	07-01-1999
		AU 6729994 A	20-12-1994
		AU 9415198 A	04-02-1999
		AU 9415398 A	04-02-1999
		CA 2159829 A	08-12-1994
		CN 1124558 A	12-06-1996
		EP 0700625 A	13-03-1996
		WO 9428683 A	08-12-1994
		SG 43106 A	17-10-1997
		JP 9504912 T	13-05-1997

EPO FORM P448

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.